

CV-2510 Part A

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Revision Date: 01/07/2021 Date of Issue: 05/20/2014



Version: 3.0

SECTION 1: Identification

1.1. Product Identifier

Product Form	Mixture
Product Name	CV-2510 Part A
Synonyms	Silicone Elastomer

1.2. Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Use of the Substance/Mixture For professional use only.

1.3. Details of the Supplier of the Safety Data Sheet

NuSil Technology LLC
1050 Cindy Lane
Carpinteria, California 93013
USA
(805) 684-8780
ehs@nusil.com
www.nusil.com

1.4. Emergency Telephone Number

Emergency Number	800-424-9300 CHEMTREC (in US); +1 703-527-3887 CHEMTREC (International and Maritime)
------------------	--

SECTION 2: Hazards Identification

2.1. Classification of the Substance or Mixture

GHS-US Classification

Aquatic Acute 2 H401

Aquatic Chronic 2 H411

Full text of hazard classes and H-statements: see section 1.6

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



GHS09

Hazard Statements (GHS-US)

H401 - Toxic to aquatic life

H411 - Toxic to aquatic life with long lasting effects

Precautionary Statements (GHS-US)

P273 - Avoid release to the environment.

P391 - Collect spillage.

P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

2.3. Other Hazards

Other Hazards Not Contributing to the Classification

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US)

No data available

CV-2510 Part A

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/Information On Ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product Identifier	%	GHS-US Classification
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	(CAS-No.) 68909-20-6	5 - 15	Not classified
Zinc oxide (ZnO)	(CAS-No.) 1314-13-2	5 - 15	Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H-phrases: see section 16

The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret [29 CFR 1910.1200].

SECTION 4: First Aid Measures

4.1. Description of First-aid Measures

First-aid Measures General	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid Measures After Inhalation	When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.
First-aid Measures After Skin Contact	Remove contaminated clothing. Drench affected area with water for at least 5 minutes. Obtain medical attention if irritation develops or persists.
First-aid Measures After Eye Contact	Rinse cautiously with water for at least 5 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.
First-aid Measures After Ingestion	Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

Symptoms/Injuries	Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/Injuries After Inhalation	Prolonged exposure may cause irritation.
Symptoms/Injuries After Skin Contact	Prolonged exposure may cause skin irritation.
Symptoms/Injuries After Eye Contact	May cause slight irritation to eyes.
Symptoms/Injuries After Ingestion	Ingestion may cause adverse effects.
Chronic Symptoms	None known.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

CV-2510 Part A

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing Media

- Suitable Extinguishing Media : Use extinguishing media appropriate for surrounding fire.
Unsuitable Extinguishing Media : Do not use a heavy water stream. Use of heavy stream of water may spread fire. Application of water stream to hot product may cause frothing and increase fire intensity.

5.2. Special Hazards Arising From the Substance or Mixture

- Fire Hazard Not considered flammable but may burn at high temperatures.
Explosion Hazard Product is not explosive.
Reactivity Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

- Precautionary Measures Fire Exercise caution when fighting any chemical fire.
Firefighting Instructions Use water spray or fog for cooling exposed containers.
Protection During Firefighting Do not enter fire area without proper protective equipment, including respiratory protection.
Hazardous Combustion Products Carbon oxides (CO, CO₂). Silicon oxides. Zinc oxides.
Other Information Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: Accidental Release Measures

6.1. Personal Precautions, Protective Equipment And Emergency Procedures

- General Measures Avoid prolonged contact with eyes, skin and clothing. Avoid breathing (vapor, mist, spray).

6.1.1. For Non-Emergency Personnel

- Protective Equipment Use appropriate personal protective equipment (PPE).
Emergency Procedures Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective Equipment Equip cleanup crew with proper protection.
Emergency Procedures Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment. Collect spillage.

6.3. Methods and Materials for Containment and Cleaning Up

- For Containment Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for Cleaning Up Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

CV-2510 Part A

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling And Storage

7.1. Precautions for Safe Handling

Precautions for Safe Handling Avoid prolonged contact with eyes, skin and clothing. Avoid breathing vapors, mist, spray. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Hygiene Measures Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures Comply with applicable regulations.

Storage Conditions Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials Strong acids, strong bases, strong oxidizers.

7.3. Specific End Use(s)

For professional use only.

SECTION 8: Exposure Controls/Personal Protection

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), or OSHA (PEL).

Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica (68909-20-6)		
USA OSHA	OSHA PEL (TWA) (mg/m ³)	6 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	20 mppcf (80 mg/m ³ /%SiO ₂)
Zinc oxide (ZnO) (1314-13-2)		
USA ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³ (respirable particulate matter)
USA ACGIH	ACGIH STEL (mg/m ³)	10 mg/m ³ (respirable particulate matter)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³ (fume) 15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)

8.2. Exposure Controls

Appropriate Engineering Controls Suitable eye/body wash equipment should be available in the vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment Gloves. Protective clothing. Protective goggles.



Materials For Protective Clothing Chemically resistant materials and fabrics.

Hand Protection Wear protective gloves.

Eye And Face Protection Chemical safety goggles.

CV-2510 Part A

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin And Body Protection	Wear suitable protective clothing.
Respiratory Protection	If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.
Other Information	When using, do not eat, drink or smoke.

SECTION 9: Physical and Chemical Properties

9.1. Information on Basic Physical and Chemical Properties

Physical State	Liquid
Appearance	White
Odor	Odorless
Odor Threshold	No data available
pH	No data available
Evaporation Rate	No data available
Melting Point	No data available
Freezing Point	No data available
Boiling Point	No data available
Flash Point	> 135 °C (> 275 °F)
Auto-ignition Temperature	No data available
Decomposition Temperature	No data available
Flammability (solid, gas)	Not applicable
Vapor Pressure	No data available
Relative Vapor Density at 20°C	No data available
Relative Density	No data available
Specific Gravity	> 1
Solubility	No data available
Partition Coefficient n-Octanol/Water	No data available
Viscosity	No data available

9.2. Other Information

VOC Content < 1%

SECTION 10: Stability and Reactivity

10.1. Reactivity

Hazardous reactions will not occur under normal conditions.

10.2. Chemical Stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

10.4. Conditions to Avoid

Direct sunlight, extremely high or low temperatures, and incompatible materials.

10.5. Incompatible Materials

Strong acids, strong bases, strong oxidizers.

10.6. Hazardous Decomposition Products

Not expected to decompose under ambient conditions.

CV-2510 Part A

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 11: Toxicological Information

11.1. Information on Toxicological Effects

Acute Toxicity (Oral) : Not classified
Acute Toxicity (Dermal) : Not classified
Acute Toxicity (Inhalation) : Not classified

Zinc oxide (ZnO) (1314-13-2)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rat	> 2000 mg/kg
Skin Corrosion/Irritation	Not classified
Serious Eye Damage/Irritation	Not classified
Respiratory or Skin Sensitization	Not classified
Germ Cell Mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive Toxicity	: Not classified
Specific Target Organ Toxicity (Single Exposure)	: Not classified
Specific Target Organ Toxicity (Repeated Exposure)	: Not classified
Aspiration Hazard	Not classified
Symptoms/Injuries After Inhalation	Prolonged exposure may cause irritation.
Symptoms/Injuries After Skin Contact	Prolonged exposure may cause skin irritation.
Symptoms/Injuries After Eye Contact	May cause slight irritation to eyes.
Symptoms/Injuries After Ingestion	Ingestion may cause adverse effects.
Chronic Symptoms	None known.

SECTION 12: Ecological Information

12.1. Toxicity

Ecology - water Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Zinc oxide (ZnO) (1314-13-2)	
LC50 Fish 1	970 µg/l (780 ug Zn/L; Exposure time: 96 h - Species: Pimephales promelas)
LC50 Fish 2	1.793 mg/l (Exposure time: 96 h - Species: Zebrafish)
NOEC Chronic Fish	0.026 mg/l (Species: Jordanella floridae)

12.2. Persistence and Degradability

CV-2510 Part A	
Persistence and Degradability	May cause long-term adverse effects in the environment.

12.3. Bioaccumulative Potential

CV-2510 Part A	
Bioaccumulative Potential	Not established.

12.4. Mobility In Soil

No additional information available

12.5. Other Adverse Effects

Other Information Avoid release to the environment.

CV-2510 Part A

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal Considerations

13.1. Waste Treatment Methods

Waste Disposal Recommendations	Dispose of contents/container in accordance with local, regional, national, and international regulations.
Additional Information	Container may remain hazardous when empty. Continue to observe all precautions.
Ecology - Waste Materials	Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: Transport Information

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT

Proper Shipping Name	ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (Zinc oxide)
Hazard Class	9
Identification Number	UN3082
Label Codes	9
Packing Group	III
Marine Pollutant	Marine pollutant
ERG Number	171




14.2. In Accordance with IMDG

Proper Shipping Name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Zinc oxide)
Hazard Class	9
Identification Number	UN3082
Packing Group	III
Label Codes	9
EmS-No. (Fire)	F-A
EmS-No. (Spillage)	S-F
Marine Pollutant	Marine pollutant



14.3. In Accordance with IATA

Proper Shipping Name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Zinc oxide)
Packing Group	III
Identification Number	UN3082
Hazard Class	9
Label Codes	9
ERG Code (IATA)	9L



CV-2510 Part A

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory Information

15.1. US Federal Regulations

All components in this mixture are listed on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, have been exempted, are not listed, not disclosed due to CBI requirements or disclosure rules according to the relevant regulation.

15.2. US State Regulations

Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica (68909-20-6)
U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term
Zinc oxide (ZnO) (1314-13-2)
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min) U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr) U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs) RTK - U.S. - Massachusetts - Right To Know List U.S. - Michigan - Occupational Exposure Limits - STELs U.S. - Michigan - Occupational Exposure Limits - TWAs U.S. - Minnesota - Hazardous Substance List U.S. - Minnesota - Permissible Exposure Limits - STELs U.S. - Minnesota - Permissible Exposure Limits - TWAs U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual RTK - U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - New York - Occupational Exposure Limits - TWAs U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour U.S. - Oregon - Permissible Exposure Limits - TWAs RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List RTK - U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Tennessee - Occupational Exposure Limits - STELs U.S. - Tennessee - Occupational Exposure Limits - TWAs U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term U.S. - Vermont - Permissible Exposure Limits - STELs U.S. - Vermont - Permissible Exposure Limits - TWAs U.S. - Washington - Permissible Exposure Limits - STELs U.S. - Washington - Permissible Exposure Limits - TWAs

SECTION 16: Other Information, Including Date of Preparation or Last Revision

Date of Preparation or Latest Revision 01/07/2021
Other Information This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1

CV-2510 Part A

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

The information provided in this Safety Data Sheet (SDS) was prepared based on data believed to be accurate as of the date of this SDS. TO THE GREATEST EXTENT PERMITTED BY LAW, NUSIL TECHNOLOGY LLC AND ITS AFFILIATED COMPANIES ("NUSIL") EXPRESSLY DISCLAIMS ANY AND ALL REPRESENTATIONS AND WARRANTIES REGARDING THE INFORMATION CONTAINED HEREIN INCLUDING, WITHOUT LIMITATION, AS TO ACCURACY, COMPLETENESS, FITNESS FOR PURPOSE OR USE, MERCHANTABILITY, NON-INFRINGEMENT, PERFORMANCE, SAFETY, SUITABILITY AND STABILITY. This SDS is intended as a guide to the appropriate use, handling, storage and disposal of the product to which it relates by properly trained personnel, and is not intended to be comprehensive. Users of NuSil's products are advised to perform their own tests and to exercise their own judgment to determine the safety, suitability and appropriate use, handling, storage and disposal of each product and product combination for their own purposes and uses. TO THE GREATEST EXTENT PERMITTED BY LAW, NUSIL DISCLAIMS LIABILITY FOR, AND BY USING NUSIL'S PRODUCTS PURCHASER AGREES THAT UNDER NO CIRCUMSTANCES SHALL NUSIL BE LIABLE FOR, SPECIAL, INDIRECT, INCIDENTAL, PUNITIVE OR CONSEQUENTIAL DAMAGES OF ANY TYPE OR KIND, INCLUDING WITHOUT LIMITATION, FOR LOSS OF PROFITS, REPUTATIONAL DAMAGE, PRODUCT RECALL OR BUSINESS INTERRUPTION.

NuSil US GHS SDS

CV-2510 Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Revision date: 01/07/2021 Date of issue: 05/20/2014

SECTION 1: Identification

1.1. Product identifier

Product form : Substance
Substance name : CV-2510 Part B
Synonyms : Curing Agent

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : For professional use only.

1.3. Details of the supplier of the safety data sheet

NuSil Technology LLC
1050 Cindy Lane
Carpinteria, California 93013
USA
(805) 684-8780
ehs@nusil.com
www.nusil.com

1.4. Emergency telephone number

Emergency number : 800-424-9300 CHEMTREC (in US); +1 703-527-3887 CHEMTREC (International and Maritime)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Skin Corr. 1C	H314
Eye Dam. 1	H318
Skin Sens. 1	H317
Muta. 2	H341
Repr. 1B	H360
STOT SE 1	H370
STOT RE 1	H372
Aquatic Acute 1	H400
Aquatic Chronic 1	H410

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Hazard statements (GHS-US) :

Danger
H314 - Causes severe skin burns and eye damage
H317 - May cause an allergic skin reaction
H341 - Suspected of causing genetic defects
H360 - May damage fertility or the unborn child
H370 - Causes damage to organs (thymus)
H372 - Causes damage to organs (thymus) through prolonged or repeated exposure
H401 - Very toxic to aquatic life
H411 - Very toxic to aquatic life with long lasting effects

CV-2510 Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary statements (GHS-US) :

- P201 - Obtain special instructions before use.
- P202 - Do not handle until all safety precautions have been read and understood.
- P260 - Do not breathe dust, fume, mist, spray, vapors.
- P264 - Wash hands, forearms, and exposed areas thoroughly after handling.
- P270 - Do not eat, drink or smoke when using this product.
- P272 - Contaminated work clothing must not be allowed out of the workplace.
- P273 - Avoid release to the environment.
- P280 - Wear eye protection, protective clothing, protective gloves.
- P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.
- P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position comfortable for breathing.
- P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P307+P311 - If exposed: Call a poison center/doctor.
- P308+P313 - If exposed or concerned: Get medical advice/attention.
- P310 - Immediately call a doctor, a POISON CENTER.
- P314 - Get medical advice/attention if you feel unwell.
- P321 - Specific treatment (see Section 4).
- P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
- P363 - Wash contaminated clothing before reuse.
- P391 - Collect spillage.
- P405 - Store locked up.
- P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

2.3. Other hazards

Other hazards not contributing to the classification : Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substance

Name	Product identifier	%	GHS-US classification
Dibutyltin dilaurate	(CAS No) 77-58-7	100	Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 2, H341 Repr. 1B, H360 STOT SE 1, H370 STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H-phrases: see section 16

3.2. Mixture

Not applicable

CV-2510 Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : If inhaled, remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.
- First-aid measures after skin contact : Immediately flush skin with plenty of water for at least 60 minutes. Remove contaminated clothing. Obtain medical attention if irritation develops or persists.
- First-aid measures after eye contact : Rinse cautiously with water for at least 60 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.
- First-aid measures after ingestion : Seek medical attention immediately. Rinse mouth. Do not induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : Causes damage to organs (thymus). Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes damage to organs (thymus) through prolonged or repeated exposure. May damage fertility. May damage the unborn child. Suspected of causing genetic defects.
- Symptoms/injuries after inhalation : Inhalation may cause immediate severe irritation progressing quickly to chemical burns.
- Symptoms/injuries after skin contact : Causes severe skin burns. May cause an allergic skin reaction.
- Symptoms/injuries after eye contact : Causes serious eye damage.
- Symptoms/injuries after ingestion : May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. Causes damage to thymus.
- Chronic symptoms : Causes damage to organs through prolonged or repeated exposure. May damage fertility. May damage the unborn child. Suspected of causing genetic defects.

4.3. Indication of any immediate medical attention and special treatment needed

If medical advice is needed, have product container or label at hand.

SECTION 5: Fire-Fighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
- Unsuitable extinguishing media : Do not use a heavy water stream. A heavy water stream may spread burning liquid. Application of water stream to hot product may cause frothing and increase fire intensity.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Not considered flammable but will burn at high temperatures.
- Explosion hazard : Product is not explosive.
- Reactivity : May react with strong oxidizers, increasing risk of fire or explosion.

5.3. Advice for firefighters

- Precautionary measures fire : Exercise caution when fighting any chemical fire.
- Firefighting instructions : Do not breathe fumes from fires or vapors from decomposition. Use water spray or fog for cooling exposed containers. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.
- Other information : Refer to Section 9 for flammability properties.

CV-2510 Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Do not get in eyes, on skin, or on clothing. Do NOT breathe vapor, mist, spray.

6.1.1. For non-emergency personnel

Protective equipment : Use appropriate personal protection equipment (PPE).
Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.
Emergency procedures : Evacuate unnecessary personnel. Ventilate area. Stop leak if safe to do so.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Clean up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material, then place in suitable container. Contact competent authorities after a spill.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : May be corrosive to metals.

Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Store in original container or corrosive resistant and/or lined container. Store in a dry, cool and well-ventilated place. Keep container tightly closed.

Incompatible products : Strong acids, strong bases, strong oxidizers.

7.3. Specific end use(s)

For professional use only.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), or OSHA (PEL).

Dibutyltin dilaurate (77-58-7)		
USA ACGIH	ACGIH chemical category	Skin - potential significant contribution to overall exposure by the cutaneous route, A4 - not classifiable as a human carcinogen

CV-2510 Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2. Exposure controls

- Appropriate engineering controls : Ensure adequate ventilation, especially in confined areas. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
- Personal protective equipment : Avoid all unnecessary exposure. Gloves. Safety glasses. Protective clothing. Face shield. Insufficient ventilation: wear respiratory protection.



- Materials for protective clothing : Corrosionproof clothing.
- Hand protection : Wear protective gloves.
- Eye protection : Chemical goggles or safety glasses. A full face shield is recommended.
- Skin and body protection : Wear suitable protective clothing. Wash contaminated clothing before reuse.
- Respiratory protection : Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.
- Environmental exposure controls : Do not allow the product to be released into the environment.
- Consumer exposure controls : Do not eat, drink or smoke during use.
- Other information : When using, do not eat, drink or smoke.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Yellow
- Odor : Slight
- Odor threshold : No data available
- pH : No data available
- Evaporation Rate : No data available
- Melting point : No data available
- Freezing point : No data available
- Boiling point : No data available
- Flash point : > 135 °C
- Auto-ignition Temperature : No data available
- Decomposition temperature : No data available
- Flammability (solid, gas) : No data available
- Vapor pressure : No data available
- Relative vapor density at 20 °C : No data available
- Specific Gravity : > 1
- Solubility : No data available
- Partition coefficient: n-octanol/water : No data available
- Viscosity : No data available

9.2. Other information

- VOC content : < 1%

SECTION 10: Stability and reactivity

10.1. Reactivity

May react with strong oxidizers, increasing risk of fire or explosion.

CV-2510 Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Ignition sources. Incompatible materials.

10.5. Incompatible materials

Strong oxidizers. Strong acids. Strong bases.

10.6. Hazardous decomposition products

Thermal decomposition generates: Carbon oxides (CO, CO₂). Oxides of tin. Irritating fumes.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Dibutyltin dilaurate (77-58-7)	
LD50 dermal rat	> 2 g/kg
Skin corrosion/irritation	: Causes severe skin burns and eye damage.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Suspected of causing genetic defects.
Carcinogenicity	: Not classified
Reproductive toxicity	: May damage fertility or the unborn child.
Specific target organ toxicity (single exposure)	: Causes damage to organs (thymus).
Specific target organ toxicity (repeated exposure)	: Causes damage to organs (thymus) through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: Inhalation may cause immediate severe irritation progressing quickly to chemical burns.
Symptoms/injuries after skin contact	: Causes severe skin burns. May cause an allergic skin reaction.
Symptoms/injuries after eye contact	: Causes serious eye damage.
Symptoms/injuries after ingestion	: May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. Causes damage to thymus.
Chronic symptoms	: Causes damage to organs through prolonged or repeated exposure (thymus). May damage fertility. May damage the unborn child. Suspected of causing genetic defects.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

Dibutyltin dilaurate (77-58-7)	
EC50 Daphnia 1	0.463 mg/l (Daphnia magna)

12.2. Persistence and degradability

Dibutyltin dilaurate (77-58-7)	
Persistence and degradability	Not established.
Dibutyltin dilaurate (77-58-7)	
Persistence and degradability	Not readily biodegradable.

CV-2510 Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.3. Bioaccumulative potential

Dibutyltin dilaurate (77-58-7)	
Bioaccumulative potential	Not established.
Dibutyltin dilaurate (77-58-7)	
Log Pow	4.44

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

- Sewage disposal recommendations : This material is hazardous to the aquatic environment. Keep out of sewers and waterways.
- Waste disposal recommendations : Dispose of waste material in accordance with all local, regional, national, and international regulations.
- Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

* The transport classification does not apply to packages smaller than 0.5L (16.9 ounces).

In accordance with DOT / IMDG / IATA

14.1. UN number

- UN-No.(DOT) : 1760
- DOT NA no. : UN1760

14.2. UN proper shipping name

- Proper Shipping Name (DOT) : Corrosive liquids, n.o.s. (dibutyltin dilaurate)
- Transport hazard class(es) (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136
- Hazard labels (DOT) : 8 - Corrosive



- DOT Symbols : G - Identifies PSN requiring a technical name
- Packing group (DOT) : III - Minor Danger
- DOT Special Provisions (49 CFR 172.102) : IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).
T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / (1 + a (tr - tf))$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees Celsius of the liquid during filling.
TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154

CV-2510 Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Packaging Non Bulk (49 CFR : 203
173.xxx)
DOT Packaging Bulk (49 CFR : 241
173.xxx)
Marine pollutant : Marine pollutant



14.3. Additional information

Emergency Response Guide (ERG) : 154
Number
Other information : No supplementary information available.

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"
EmS-No. (1) : F-A
MFAG-No : 154
EmS-No. (2) : S-B

Air transport

DOT Quantity Limitations Passenger : 5 L
aircraft/rail (49 CFR 173.27)
DOT Quantity Limitations Cargo : 60 L
aircraft only (49 CFR 175.75)

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed or exempted from being listed on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Dibutyltin dilaurate (77-58-7)	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard

15.2. US State regulations

Dibutyltin dilaurate (77-58-7)
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

SECTION 16: Other information, including date of preparation or last revision

Revision date : 01/07/2021
Other information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

Full text of H-phrases:

Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Muta. 2	Germ cell mutagenicity Category 2
Repr. 1B	Reproductive toxicity Category 1B
Skin Corr. 1C	Skin corrosion/irritation Category 1C
Skin Sens. 1	Skin sensitization Category 1


CV-2510 Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H341	Suspected of causing genetic defects
H360	May damage fertility or the unborn child
H370	Causes damage to organs
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

- NFPA health hazard : 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.
- NFPA fire hazard : 1 - Must be preheated before ignition can occur.
- NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



The information provided in this Safety Data Sheet (SDS) was prepared based on data believed to be accurate as of the date of this SDS. TO THE GREATEST EXTENT PERMITTED BY LAW, NUSIL TECHNOLOGY LLC AND ITS AFFILIATED COMPANIES ("NUSIL") EXPRESSLY DISCLAIMS ANY AND ALL REPRESENTATIONS AND WARRANTIES REGARDING THE INFORMATION CONTAINED HEREIN INCLUDING, WITHOUT LIMITATION, AS TO ACCURACY, COMPLETENESS, FITNESS FOR PURPOSE OR USE, MERCHANTABILITY, NON-INFRINGEMENT, PERFORMANCE, SAFETY, SUITABILITY AND STABILITY. This SDS is intended as a guide to the appropriate use, handling, storage and disposal of the product to which it relates by properly trained personnel, and is not intended to be comprehensive. Users of NuSil's products are advised to perform their own tests and to exercise their own judgment to determine the safety, suitability and appropriate use, handling, storage and disposal of each product and product combination for their own purposes and uses. TO THE GREATEST EXTENT PERMITTED BY LAW, NUSIL DISCLAIMS LIABILITY FOR, AND BY USING NUSIL'S PRODUCTS PURCHASER AGREES THAT UNDER NO CIRCUMSTANCES SHALL NUSIL BE LIABLE FOR, SPECIAL, INDIRECT, INCIDENTAL, PUNITIVE OR CONSEQUENTIAL DAMAGES OF ANY TYPE OR KIND, INCLUDING WITHOUT LIMITATION, FOR LOSS OF PROFITS, REPUTATIONAL DAMAGE, PRODUCT RECALL OR BUSINESS INTERRUPTION.

NuSil US GHS SDS