

CV-2943 Part A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 04/26/2016

Date of issue: 11/18/2013

Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : CV-2943 Part A
Synonyms : Thermally Conductive, Controlled Volatility RTV Silicone

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : To provide moderate heat transfer between electrical/electronic components and their heat sinks. For professional use only.

1.3. Details of the supplier of the safety data sheet

NuSil Technology LLC
1050 Cindy Lane
Carpinteria, California 93013
USA
(805) 684-8780
ehs@nusil.com
www.nusil.com

1.4. Emergency telephone number

Emergency number : 800-424-9300 CHEMTREC (in US); (703) 527-3887 CHEMTREC (outside US)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Not classified

2.2. Label elements

GHS-US labeling

No labeling applicable

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Aluminum oxide	(CAS No) 1344-28-1	80 - 85	Comb. Dust, H232

Full text of H-phrases: see section 16

CV-2943 Part A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).
- First-aid measures after inhalation : Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.
- First-aid measures after skin contact : Rinse immediately with plenty of water. Obtain medical attention if irritation develops or persists.
- First-aid measures after eye contact : Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.
- First-aid measures after ingestion : Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : Not expected to present a significant hazard under anticipated conditions of normal use.
- Symptoms/injuries after inhalation : May cause respiratory irritation.
- Symptoms/injuries after skin contact : May cause skin irritation.
- Symptoms/injuries after eye contact : May cause eye irritation.
- Symptoms/injuries after ingestion : Ingestion is likely to be harmful or have adverse effects.
- Chronic symptoms : None expected under normal conditions of use.

4.3. Indication of any immediate medical attention and special treatment needed

If you feel unwell, seek medical advice (show the label where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
- Unsuitable extinguishing media : Do not use a heavy water stream. Use of heavy stream of water may spread fire. Application of water stream to hot product may cause frothing and increase fire intensity.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Not considered flammable but may burn at high temperatures.
- Explosion hazard : Product is not explosive.
- Reactivity : Hazardous reactions will not occur under normal conditions.

5.3. Advice for firefighters

- Precautionary measures fire : Exercise caution when fighting any chemical fire.
- Firefighting instructions : Use water spray or fog for cooling exposed containers.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.
- Other information : Refer to Section 9 for flammability properties.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Avoid all contact with skin, eyes, or clothing. Avoid breathing (dust, vapor, mist, gas).

6.1.1. For non-emergency personnel

- Protective equipment : Use appropriate personal protection equipment (PPE).
- Emergency procedures : Evacuate unnecessary personnel.

CV-2943 Part A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Stop leak if safe to do so. Eliminate ignition sources. Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
- Methods for cleaning up : Clear up spills immediately and dispose of waste safely. Spills should be contained with mechanical barriers. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Comply with applicable regulations.
- Storage conditions : Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.
- Incompatible products : Strong acids. Strong bases. Strong oxidizers.

7.3. Specific end use(s)

For professional use only.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Aluminum oxide (1344-28-1)		
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³

8.2. Exposure controls

- Appropriate engineering controls : Ensure adequate ventilation, especially in confined areas. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed.
- Personal protective equipment : Protective goggles. Gloves. Protective clothing.



- Materials for protective clothing : Chemically resistant materials and fabrics.
- Hand protection : Wear chemically resistant protective gloves.
- Eye protection : Chemical goggles or safety glasses.
- Skin and body protection : Wear suitable protective clothing.
- Respiratory protection : Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.
- Environmental exposure controls : Do not allow the product to be released into the environment.
- Consumer exposure controls : Do not eat, drink or smoke during use.

CV-2943 Part A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Gray
Odor	: Odorless.
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 375 °C (527 °F)
Self ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 2.5
Specific Gravity	: No data available
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content : < 1 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Hazardous reactions will not occur under normal conditions.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Ignition sources. Incompatible materials.

10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizers.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO₂). Silicon oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

CV-2943 Part A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Aluminum oxide (1344-28-1)	
LD50 oral rat	> 5000 mg/kg

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: May cause respiratory irritation.
Symptoms/injuries after skin contact	: May cause skin irritation.
Symptoms/injuries after eye contact	: May cause eye irritation.
Symptoms/injuries after ingestion	: Ingestion is likely to be harmful or have adverse effects.
Chronic symptoms	: None expected under normal conditions of use.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose of waste material in accordance with all local, regional, national, and international regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT / IMDG / IATA

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Additional information

Other information : No supplementary information available.

CV-2943 Part A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

Aluminum oxide (1344-28-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on SARA Section 313 (Specific toxic chemical listings)	
SARA Section 313 - Emission Reporting	1.0 % (fibrous forms)

15.3. US State regulations

Aluminum oxide (1344-28-1)
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
U.S. - Idaho - Occupational Exposure Limits - TWAs
U.S. - Massachusetts - Right To Know List
U.S. - Massachusetts - Toxics Use Reduction Act
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Environmental Hazardous Substances List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Oregon - Permissible Exposure Limits - TWAs
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
U.S. - Vermont - Permissible Exposure Limits - TWAs
U.S. - Washington - Permissible Exposure Limits - STELs
U.S. - Washington - Permissible Exposure Limits - TWAs

SECTION 16: Other information

Revision date : 04/26/2016

Other information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

Full text of H-phrases: see section 16:

Comb. Dust	Combustible Dust
Eye Irrit. 2B	Serious eye damage/eye irritation Category 2B
H232	May form combustible dust concentrations in air

CV-2943 Part A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H320

Causes eye irritation

NFPA health hazard


0 - Exposure under fire conditions would offer no hazard beyond that of ordinary combustible materials.

NFPA fire hazard

1 - Must be preheated before ignition can occur.

NFPA reactivity

0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



We believe that the information contained herein is current as of the date of this Safety Data Sheet, and is offered in good faith. Since the use of this information and of these opinions and the conditions of the use of the product are not within the control of NuSil Technology, it is the user's obligation to determine the conditions of safe use of the product.

SDS US (GHS HazCom 2012)

CV-2943 Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Revision date: 04/26/2016 Date of issue: 07/15/2014

Version: 2.0

SECTION 1: Identification

1.1. Product identifier

Product form : Substance
Substance name : CV-2943 Part B
CAS No : 77-58-7
Synonyms : Organotin

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : For professional use only.

1.3. Details of the supplier of the safety data sheet

NuSil Technology LLC
1050 Cindy Lane
Carpinteria, California 93013
USA
(805) 684-8780
ehs@nusil.com
www.nusil.com

1.4. Emergency telephone number

Emergency number : 800-424-9300 CHEMTREC (in US); +1 703-527-3887 CHEMTREC (International and Maritime)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Skin Corr. 1C H314
Eye Dam. 1 H318
Skin Sens. 1 H317
Muta. 2 H341
Repr. 1B H360
STOT SE 1 H370
STOT RE 1 H372
Aquatic Acute 1 H400
Aquatic Chronic 1 H410
Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H314 - Causes severe skin burns and eye damage
H317 - May cause an allergic skin reaction
H341 - Suspected of causing genetic defects
H360 - May damage fertility or the unborn child
H370 - Causes damage to organs (thymus)
H372 - Causes damage to organs (thymus) through prolonged or repeated exposure
H400 - Very toxic to aquatic life

CV-2943 Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary statements (GHS-US)

H410 - Very toxic to aquatic life with long lasting effects
P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P260 - Do not breathe dust, fume, mist, spray, vapors.
P264 - Wash hands, forearms, and exposed areas thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear eye protection, protective clothing, protective gloves.
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P307+P311 - If exposed: Call a poison center/doctor.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P310 - Immediately call a doctor, a POISON CENTER.
P314 - Get medical advice/attention if you feel unwell.
P321 - Specific treatment (see Section 4).
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P363 - Wash contaminated clothing before reuse.
P391 - Collect spillage.
P405 - Store locked up.
P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

2.3. Other hazards

Other hazards not contributing to the classification : Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substance

Name : CV-2943 Part B
CAS No : 77-58-7

Name	Product identifier	%	GHS-US classification
Dibutyltin dilaurate	(CAS No) 77-58-7	100	Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 2, H341 Repr. 1B, H360 STOT SE 1, H370 STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

CV-2943 Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases: see section 16

3.2. Mixture

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : If inhaled, remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.
- First-aid measures after skin contact : Immediately flush skin with plenty of water for at least 60 minutes. Remove contaminated clothing. Obtain medical attention if irritation develops or persists.
- First-aid measures after eye contact : Rinse cautiously with water for at least 60 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.
- First-aid measures after ingestion : Seek medical attention immediately. Rinse mouth. Do not induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : Causes damage to organs (thymus). Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes damage to organs (thymus) through prolonged or repeated exposure. May damage fertility. May damage the unborn child. Suspected of causing genetic defects.
- Symptoms/injuries after inhalation : Inhalation may cause immediate severe irritation progressing quickly to chemical burns.
- Symptoms/injuries after skin contact : Causes severe skin burns. May cause an allergic skin reaction.
- Symptoms/injuries after eye contact : Causes serious eye damage.
- Symptoms/injuries after ingestion : May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. Causes damage to thymus.
- Chronic symptoms : Causes damage to organs through prolonged or repeated exposure. May damage fertility. May damage the unborn child. Suspected of causing genetic defects.

4.3. Indication of any immediate medical attention and special treatment needed

If medical advice is needed, have product container or label at hand.

SECTION 5: Fire-Fighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
- Unsuitable extinguishing media : Do not use a heavy water stream. A heavy water stream may spread burning liquid. Application of water stream to hot product may cause frothing and increase fire intensity.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Not considered flammable but will burn at high temperatures.
- Explosion hazard : Product is not explosive.
- Reactivity : May react with strong oxidizers, increasing risk of fire or explosion.

5.3. Advice for firefighters

- Precautionary measures fire : Exercise caution when fighting any chemical fire.

CV-2943 Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Firefighting instructions	: Do not breathe fumes from fires or vapors from decomposition. Use water spray or fog for cooling exposed containers. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: Refer to Section 9 for flammability properties.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Do not get in eyes, on skin, or on clothing. Do NOT breathe vapor, mist, spray.

6.1.1. For non-emergency personnel

Protective equipment : Use appropriate personal protection equipment (PPE).

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Evacuate unnecessary personnel. Ventilate area. Stop leak if safe to do so.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Clean up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material, then place in suitable container. Contact competent authorities after a spill.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : May be corrosive to metals.

Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Store in original container or corrosive resistant and/or lined container. Store in a dry, cool and well-ventilated place. Keep container tightly closed.

Incompatible products : Strong acids, strong bases, strong oxidizers.

7.3. Specific end use(s)

For professional use only.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), or OSHA (PEL).

CV-2943 Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Dibutyltin dilaurate (77-58-7)		
USA ACGIH	ACGIH chemical category	Skin - potential significant contribution to overall exposure by the cutaneous route, A4 - not classifiable as a human carcinogen

8.2. Exposure controls

- Appropriate engineering controls : Ensure adequate ventilation, especially in confined areas. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
- Personal protective equipment : Avoid all unnecessary exposure. Gloves. Safety glasses. Protective clothing. Face shield. Insufficient ventilation: wear respiratory protection.



- Materials for protective clothing : Corrosionproof clothing.
- Hand protection : Wear protective gloves.
- Eye protection : Chemical goggles or safety glasses. A full face shield is recommended.
- Skin and body protection : Wear suitable protective clothing. Wash contaminated clothing before reuse.
- Respiratory protection : Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.
- Environmental exposure controls : Do not allow the product to be released into the environment.
- Consumer exposure controls : Do not eat, drink or smoke during use.
- Other information : When using, do not eat, drink or smoke.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Translucent Yellow
- Odor : Slight
- Odor threshold : No data available
- pH : No data available
- Evaporation Rate : No data available
- Melting point : No data available
- Freezing point : No data available
- Boiling point : > 204.4 °C (> 400 °F)
- Flash point : 235 °C (455 °F)
- Auto-ignition Temperature : No data available
- Decomposition temperature : No data available
- Flammability (solid, gas) : No data available
- Vapor pressure : No data available
- Relative vapor density at 20 °C : No data available
- Specific Gravity : 1.05
- Solubility : No data available
- Partition coefficient: n-octanol/water : No data available
- Viscosity : No data available

9.2. Other information

- VOC content : < 1 %

CV-2943 Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

May react with strong oxidizers, increasing risk of fire or explosion.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Ignition sources. Incompatible materials.

10.5. Incompatible materials

Strong oxidizers. Strong acids. Strong bases.

10.6. Hazardous decomposition products

Thermal decomposition generates: Carbon oxides (CO, CO₂). Oxides of tin. Irritating fumes.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

CV-2943 Part B (77-58-7)

Dibutyltin dilaurate (77-58-7)

LD50 dermal rat : > 2 g/kg

Skin corrosion/irritation : Causes severe skin burns and eye damage.

Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitization : May cause an allergic skin reaction.

Germ cell mutagenicity : Suspected of causing genetic defects.

Carcinogenicity : Not classified

Reproductive toxicity : May damage fertility or the unborn child.

Specific target organ toxicity (single exposure) : Causes damage to organs (thymus).

Specific target organ toxicity (repeated exposure) : Causes damage to organs (thymus) through prolonged or repeated exposure.

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : Inhalation may cause immediate severe irritation progressing quickly to chemical burns.

Symptoms/injuries after skin contact : Causes severe skin burns. May cause an allergic skin reaction.

Symptoms/injuries after eye contact : Causes serious eye damage.

Symptoms/injuries after ingestion : May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. Causes damage to thymus.

Chronic symptoms : Causes damage to organs through prolonged or repeated exposure (thymus). May damage fertility. May damage the unborn child. Suspected of causing genetic defects.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

Dibutyltin dilaurate (77-58-7)

EC50 Daphnia 1 : 0.463 mg/l (Daphnia magna)

CV-2943 Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.2. Persistence and degradability

CV-2943 Part B (77-58-7)

Persistence and degradability : Not established.

Dibutyltin dilaurate (77-58-7)

Persistence and degradability : Not readily biodegradable.

12.3. Bioaccumulative potential

CV-2943 Part B (77-58-7)

Bioaccumulative potential : Not established.

Dibutyltin dilaurate (77-58-7)

Log Pow : 4.44

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations : This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

Waste disposal recommendations : Dispose of waste material in accordance with all local, regional, national, and international regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

*** The transport classification does not apply to packages smaller than 0.5L (16.9 ounces).**

In accordance with DOT / IMDG / IATA

14.1. UN number

UN-No.(DOT) : 1760

DOT NA no. : UN1760

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Corrosive liquids, n.o.s. (Dibutyltin dilaurate)

Transport hazard class(es) (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

Hazard labels (DOT) : 8 - Corrosive



DOT Symbols : G - Identifies PSN requiring a technical name

Packing group (DOT) : III - Minor Danger

CV-2943 Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	: IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / (1 + a (tr - tf))$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 154
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 241
Marine pollutant	: Marine pollutant



14.3. Additional information

Emergency Response Guide (ERG) Number	: 154
Other information	: No supplementary information available.

Transport by sea

DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"
EmS-No. (1)	: F-A
MFAG-No	: 154
EmS-No. (2)	: S-B

Air transport

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed or exempted from being listed on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

CV-2943 Part B (77-58-7)	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard

15.2. US State regulations

CV-2943 Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Dibutyltin dilaurate (77-58-7)

U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

SECTION 16: Other information, including date of preparation or last revision

Revision date : 04/26/2016
Other information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

Full text of H-phrases:


Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Muta. 2	Germ cell mutagenicity Category 2
Repr. 1B	Reproductive toxicity Category 1B
Skin Corr. 1C	Skin corrosion/irritation Category 1C
Skin Sens. 1	Skin sensitization Category 1
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H341	Suspected of causing genetic defects
H360	May damage fertility or the unborn child
H370	Causes damage to organs
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

CV-2943 Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA health hazard	3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.
NFPA fire hazard	1 - Must be preheated before ignition can occur.
NFPA reactivity	0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



We believe that the information contained herein is current as of the date of this Safety Data Sheet, and is offered in good faith. Since the use of this information and of these opinions and the conditions of the use of the product are not within the control of NuSil Technology, it is the user's obligation to determine the conditions of safe use of the product.

Nusil US GHS SDS